



DRILLFORM

FORMING THE FUTURE OF DRILLING EQUIPMENT



BULLDOG

SC710 SERVICE CATWALK



FEATURES & BENEFITS

EASE OF TRANSPORT | A simple setup, the SC710 transitions seamlessly to transport mode

COST SAVINGS | Faster cycle times and a higher lift capacity

EASE OF USE | Rigged up in minutes, the unit can be towed via pintle hitch and is designed to fit a 40' container

SAFETY | Lower recordable incidents are achieved by reducing dropped objects and repetitive lifting

DRILLFORM.COM | SALES@DRILLFORM.COM | +1 (403) 263 3133

BULLDOG



SC710 TECHNICAL SPECIFICATIONS

Tubular Handling for Service Rigs

The volume of tubulars requiring safe handling increases with longer reach horizontals and Drillform's base model offers speed, safety and simplicity.

Drillform's Bulldog SC710 Service Catwalk operates conveniently on rig air to increase safety and ease of pipe handling on workover rigs. It accommodates rig floor heights from 7' to 12' high with adjustable pipe racks and an extended pipe channel to accommodate Range II and Range III tubulars. This towable catwalk has a pintle hitch for easy towing and is available in a skid version.

The SC710 is simple to set up and has the ability to transition into transport mode for longer hauls.



PIPE RACK CAPACITY

Length: 16' 6" / 5.1 m
Max Capacity: 15,000 lbs each / 6,800 kg each
Adjustable Pipe Racks for Range II & Range III Tubulars

HITCH WEIGHT

Range II & III Configuration: 1,830 lbs / 830 kg
Range II Configuration: 1,526 lbs / 690 kg
Full transport: 885 lbs / 401 kg

TRANSPORTATION

Dimensions (LxWxH): 40' x 7' x 7'1" / 12 m x 2.1 m x 2.16 m
Transportation Weight: 11,000 lbs / 4,900 kg
Two 7,000 lbs / 3,175kg Axles

TUBULAR CAPACITY

OD: 1" to 6" / 25 mm to 152 mm
Range II & Range III
Weight: 1,500 lbs / 680 kg

